



Rigid-Lock QuickBerm® Spill Containment Berms

Innovative, cost-effective spill control for drums, IBCs, vehicles, tankers, and more

their safety is essential.
Protecting people, property, and the planet.

Convenient & Efficient:

- Single piece construction deploys quickly—no assembly needed
- Sidewalls lower easily for convenient access
- Unobstructed workspace inside berm reduces tripping hazards
- Flexible design folds for easy shipping, portability, and storage

Reliable Protection:

- 100% leakproof protection
- Reinforced CriticalCorner™ design prevents seam leaks
- Complies with EPA for containment and spill prevention (SPCC)—protect the environment while avoiding costly fines and hazardous clean-up costs
- Reduces slip and fall accidents

Superior Design & Performance:

- Patented, built-in stainless-steel wall supports lock into place and do not sag
- High-strength nylon support hub includes anchor holes to withstand winds up to 40 MPH (anchors not included)
- In down position, supports withstand vehicle weights up to 11,000 lb (5,000 kg) per tire
- Fray-resistant top hem adds strength and integrity
- BCI's PVC coated fabric provides UV and chemical resistance
- Rigid-Lock QuickBerm All-in-One models include integral track runners on top and bottom of berm for added protection



Rigid-Lock QuickBerm



Rigid-Lock QuickBerm All-in-One



Rigid-Lock QuickBerm



Rigid-Lock QuickBerm Lite

	Rigid-Lock QuickBerm® Lite	Rigid-Lock QuickBerm®	Rigid-Lock QuickBerm® All-in-One
Material	BC1CF PVC coated fabric	BC2.8CF modified PVC coated fabric	BC2.8CF modified PVC coated fabric with welded-in track runners
Abrasion resistance	Good	Better	Best
Chemical resistance	Good	Better	Better
Puncture resistance	Good	Better	Best
Wall height	8 inches	12 inches	12 inches
Vehicle traffic	None	Medium to low frequency	High frequency
Usage	Short term / emergency	Long term	Long term / rental
Color	Yellow	Black	Black and yellow
Warranty	1-year limited	5-year limited	5-year limited



Rigid-Lock QuickBerm® Models

Capacity (gallons/liters)	Nominal Inside Dimensions (W x D x H)	Model
Rigid-Lock QuickBerm® Lite - for emergency and low frequency use applications		
79/299	4 ft x 4 ft x 8in (1.2m x 1.2m x 203mm)	1054-03654-106
119/451	4 ft x 6 ft x 8in (1.2m x 1.8m x 203mm)	1054-03655-106
159/602	4 ft x 8 ft x 8in (1.2m x 2.4m x 203mm)	1054-04134-106
318/1204	8 ft x 8 ft x 8in (2.4m x 2.4m x 203mm)	1054-03657-106
398/1507	8 ft x 10 ft x 8in (2.4m x 3.0m x 203mm)	1054-03658-106



Rigid-Lock QuickBerm Lite

Rigid-Lock QuickBerm® - for pedestrian and low frequency drive-in / drive-out applications		
175/662	4 ft x 6 ft x 12in (1.2m x 1.8m x 305mm)	1050-01746-026
235/890	4 ft x 8 ft x 12in (1.2m x 2.4m x 305mm)	1050-01950-026
355/1344	6 ft x 8 ft x 12in (1.8m x 2.4m x 305mm)	1050-01931-026
475/1798	8 ft x 8 ft x 12in (2.4m x 2.4m x 305mm)	1050-02234-026
745/2820	10 ft x 10 ft x 12in (3.0m x 3.0m x 305mm)	1050-01799-026
1075/4069	12 ft x 12 ft x 12in (3.7m x 3.7m x 305mm)	1050-01861-026
1435/5432	12 ft x 16 ft x 12in (3.7m x 4.9m x 305mm)	1050-02177-026
1795/6795	12 ft x 20 ft x 12in (3.7m x 6.1m x 305mm)	1050-02040-026
1910/7230	16 ft x 16 ft x 12in (4.9m x 4.9m x 305mm)	1050-02919-026
2390/9047	16 ft x 20 ft x 12in (4.9m x 6.1m x 305mm)	1050-02279-026
2510/9501	12 ft x 28 ft x 12in (3.7m x 8.5m x 305mm)	1050-01835-026
2990/11318	20 ft x 20 ft x 12in (6.1m x 6.1m x 305mm)	1050-02486-026
4485/16978	12 ft x 50 ft x 12in (3.7m x 15.2m x 305mm)	1050-01805-026
4840/18321	12 ft x 54 ft x 12in (3.7m x 16.5m x 305mm)	1050-02612-026
5860/22183	14 ft x 56 ft x 12in (4.3m x 17.1m x 305mm)	1050-02152-026



Rigid-Lock QuickBerm

Rigid-Lock QuickBerm® All-in-One - for higher frequency vehicle applications		
595/2252	8 ft x 10 ft x 12in (2.4m x 3.0m x 305mm)	1065-04638-026
1120/4240	10 ft x 15 ft x 12in (3.0m x 4.6m x 305mm)	1065-04639-026
2510/9501	12 ft x 28 ft x 12in (3.7m x 8.5m x 305mm)	1065-04640-026
4485/16978	12 ft x 50 ft x 12in (3.7m x 15.2m x 305mm)	1065-04641-026
4840/18321	12 ft x 54 ft x 12in (3.7m x 16.5m x 305mm)	1065-04642-026
5860/22183	14 ft x 56 ft x 12in (4.3m x 17.1m x 305mm)	1065-04643-026

Note (1): For exterior dimension, add 8-in (203-mm) to width and length to account for support and hub.

Note (2): When selecting a berm size, allow 12-in (305-mm) at entry or exit for lowering and raising the wall on Rigid-Lock QuickBerm and Rigid-Lock QuickBerm All-in-One models.

Note (3): When selecting a berm size, allow 8-in (203-mm) at entry or exit for lowering and raising the wall on Rigid-Lock QuickBerm Lite models.



Rigid-Lock QuickBerm All-in-One

Quick-deploy design for permanent or temporary spill control



No assembly needed—saves time, ready in minutes!



Rigid-Lock QuickBerm All-in-One